



**Model: BHW**


## BRAKE HAND WINCHES

### Technical Specialities

- The cost - effective solution for a wide variety of applications, ABLE Brake Hand Winches can be used to pull or lift loads.
- Positive action brake can hold the load in any position
- Compact, light weight and rugged construction
- Mechanical components enclosed for protection
- Baked enamel finish for corrosion protection
- Rope to drum fixing clamp provided
- Available in corrosion resistant grade 304 stainless steel
- stainless model available in BHW range



Double brake pawl for extra safety on BHW-1800 and BHW-2600 models.



Gears are strong, durable and electroplated for extra corrosion resistance.



SF-2200  
Ideal for use in confined locations, the ratchet handle permits reciprocating handle movement in both directions for hoisting and lowering loads.



HW-1500  
Worm drive non-brake



**AS1418.2 Compliance applies when fitted with Approved Wire Ropes and Fittings.**

MODEL	BHW-800	BHW-1200	BHW-1800	BHW-2600	SF-2200	HW-1500
Capacity (kg) Pull-Lift	370-180	545-270	820-410	1200-600	1100	680
Hand force required kg	14.5	15	22	19	16	4.5
Gear ratio	4.1:1	4.1:1	5:1	10:1	22.2:1	41:1
Hub diameter mm	φ40	φ50	φ70	φ80	φ60	φ48
Handle length mm	160	210	320	320	300	195
Unit weight kg	3	3.3	8	10.3	13.5	4.9
Rope diameter mm	φ4	φ5	φ7	φ8	φ8	φ4
Rops storage capacity m	36	23	24	18	35	23

ABLE  
Hand Winches